

c1  
(without adding any address information) scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

decoding the communication mark to obtain at least a first communication address for a first communication mode and a second communication address for a second different type of communication mode directly or indirectly from said communication mark;

selecting one of the communication addresses and inputting said selected communication address into an address function of a communication device; and

initiating a communication of said information to said communication address through said communication device.

537 1. (Twice Amended) A method for providing automatic communication addressing comprising the steps of:

c2  
receiving a document from one from the group of a fax and an email communication and creating a hardcopy of the document;

without adding any address information, scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

decoding the communication mark to obtain at least one Internet address from said communication mark;

automatically accessing a site for the Internet address and retrieving at least one communications address;

inputting said communication address into an address function of a communication device; and

initiating a communication of said information to said communication address through said communication device;

wherein said communication mark is a storage address to a location where a communication address is stored.

5208 25. (NEW) A program product for providing automatic communication addressing, comprising machine-readable program code for causing a machine to perform the following method:

receiving a document from one from the group of a fax and an email communication and creating a hardcopy of the document;

C3 without adding any address information, scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

decoding the communication mark to obtain at least a first communication address for a first communication mode and a second communication address for a second different type of communication mode directly or indirectly from said communication mark;

selecting one of the communication addresses and inputting said selected communication address into an address function of a communication device; and

initiating a communication of said information to said communication address through said communication device.

525 f1 26. (NEW) A program product for providing automatic communication addressing, comprising machine-readable program code for causing a machine to perform the following method:

receiving a document from one from the group of a fax and an email communication and creating a hardcopy of the document;

without adding any address information, scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

decoding the communication mark to obtain at least one Internet address from said communication mark;

automatically accessing a site for the Internet address and retrieving at least one communications address;

inputting said communication address into an address function of a communication device; and

initiating a communication of said information to said communication address through said communication device.

539 } 27. (NEW) A system for providing automatic communication addressing comprising:

C3 logic for receiving a document from one from the group of a fax and an email communication and creating a hardcopy of the document;

logic for, without adding any address information, scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

logic for decoding the communication mark to obtain at least a first communication address for a first communication mode and a second communication address for a second different type of communication mode directly or indirectly from said communication mark;

logic for selecting one of the communication addresses and inputting said selected communication address into an address function of a communication device; and

logic for initiating a communication of said information to said communication address through said communication device.

5.5 Fi } 28. (NEW) A system for providing automatic communication addressing comprising:

logic for receiving a document from one from the group of a fax and an email communication and creating a hardcopy of the document;

logic for, without adding any address information, scanning the document to obtain at least one communication mark, if one is present, on the hardcopy;

logic for decoding the communication mark to obtain at least one Internet address from said communication mark;

C3 logic for automatically accessing a site for the Internet address and retrieving at least one communications address;

logic for inputting said communication address into an address function of a communication device; and

logic for initiating a communication of said information to said communication address through said communication device.